

PG 20-100

HV-Pulse Generator
Impulse voltage tests of Solar Modules

Voltage	0.8 – 20 kV
Waveform	1.2 / 50 μs
Range of EUT capacitances	10 nF – 183 nF



According to
IEC 61730-2 Ed 2.0 (2016)

The HV-Pulse generator PG20-100 is used for impulse voltage tests of solar modules (photovoltaic panels) with the standard surge voltage waveform 1.2/50 μ s according to IEC 60060-1/2 up to 20 kV acc. to IEC 61730-2.

Sales Partner:



ABSOLUTE EMC LLC.
 Covering sales in North America
 United States, Mexico, & Canada

absolute-emc.com
 Phone:703-774-7505
 info@absolute-emc.com

02/18
 Page 1 of 3
www.hilo-test.de

For the surge voltage tests of solar modules, these are enveloped with a copper foil as described in the relative above standard. After that the connections of the solar modules are tested with surge voltage against the copper foils. The tight copper foil envelope required by the standard results in comparatively high capacitances of approx. 10 - 183 nF, which is switched in parallel to the output of the impulse generator.

Therefore, a special impulse voltage generator is required for this standard specified test, which can generate the specified impulse wave shapes for the different EUT-capacitances, which are a result of the varying dimension of the solar modules to be tested.

The high voltage Pulse Generator comprises 5 different pulse forming networks, which allow to generate the requested wave shapes fully complying with the tolerances specified in the standard for the different EUT capacitances.

The PG 20-100 excels by its compact design, simple handling and precise reproducibility of the test impulses. The pulse forming Networks are equipped with maintenance-free semiconductor switches.

The generator features a microprocessor controlled user interface and a 7" touch screen unit for ease of use. The microprocessor allows the user to execute either standard test routines or a "user defined" test sequence. The test parameters which are shown on the built in display, are easily adjusted by means of touch screen.

A standard USB port provides the ability to print a summary of the test parameters to a USB stick.

Moreover, all generator functions may be computer controlled.

The software program PG-REMOTE allows full remote control of the test generator via fiber optic Ethernet interface as well as documentation and evaluation of test results, accordingly to the IEC 17025. To record definite impulses, it is equipped with an Impulse Recording Function (IRF)

Sales Partner:



ABSOLUTE EMC LLC.
Covering sales in North America
United States, Mexico, & Canada

absolute-emc.com
Phone: 703-774-7505
info@absolute-emc.com

Page 2 of 3
www.hilo-test.de

TECHNICAL SPECIFICATIONS		PG 20-100
Mainframe		
Microprocessor controlled touch panel		7", capacitive
Optical Ethernet Interface for remote control of the generator		optional
Interface for saving reports		USB
External trigger input/ output		Switch/ 10 V
Connector for external safety interlock loop		24 V =
External red and green warning lamps		230 V, 60W
Mains power		90V - 264V, 50/60 Hz
Dimensions of desk top case W * H * D		450*330*500 mm ³
Weight		30 kg
High- Voltage Pulse Generator acc. to IEC 61720-2		
Impulse output voltage, adjustable		0.8 - 20 kV (± 3%)
Waveform of Impulse output voltage		1.2 / 50 µs (±30% / ±20%)
Polarity, selectable per software (no plugs necessary)		pos./neg.
Maximum stored energy Cs		100J
Charging time for max. charging voltage		approx. 10s
Interior load capacitance Cp		10 nF (± 10%)
Pulse forming networks to test solar modules:		Cp = 10 - 183nF
selectable per software (no plugs necessary)		
Area	EUT capacitances nominal	Range of EUT capacitances
1	12 nF	10 - 16 nF
2	22 nF	16 - 27 nF
3	33 nF	27 - 40 nF
4	47 nF	40 - 57 nF
5	68 nF	57 - 83 nF
6	100 nF	83 - 122 nF
7	150 nF	122 - 183 nF
Spark-over detection:		PASS / FAIL
Impulse current output: on the generator's rear panel		HV conector
Impulse high voltage dividers to observe the impulse wave shape ratio		built-in 1000 : 1 ±2%
Accessories		
mains cable, key, HV-connection cable, operation instructions		

Options	PG 20-100
Software PG-REMOTE, for remote control	
With Impulse Recording Function (IRF)	
(XP, WIN7, WIN10) incl. 5 m fibre optic cable and PC Ethernet interface	
Capacitor- calibration- kit	
Calibration capacities:	CCK 20 23nF, 33nF, 50nF, 73nF, 100nF, 156nF (±3%)

Sales Partner:



ABSOLUTE EMC Llc.
Covering sales in North America
United States, Mexico, & Canada

absolute-emc.com
Phone: 703-774-7505
info@absolute-emc.com