

Compact Antenna Mast CAM 6.0 - P - 12kg

Technical data:

| | |
|---|--|
| Antenna height automatic adjustable | 1.0 m - 6.0 m |
| Total mast height | 6.5 m |
| Load capability | max. 12 kg (when balanced) |
| For long and heavy antennas, a counter weight is required to balancing the load. Depending on the distance of the antenna gravity center | |
| Material of antenna mast | Plastic and reinforced fiberglass |
| Mast cross section | 101 mm x 95 mm |
| Base L x W | 1.3 m x 0.7 m |
| Position speed adjustable | |
| in combination with FCU3.0 | 1.0 cm/s - 35 cm/s |
| in combination with NCD | 1.0 cm/s - 20 cm/s |
| Position accuracy | +/- 0.5 cm |
| Pneumatic polarization | 0° / 90° (vert. / hor.) |
| Polarization time | approx. 3 s |
| Polarization drive | Pneumatic rotary actuator |
| Control | Solenoid valve |
| Nominal pressure | max. 6 bar |
| Motor | DC stepper Motor |
| Antenna support drive | Toothed belt |
| Material of toothed belts | Kevlar reinforced (non-metallic) |
| Voltage | 110 VAC - 230 VAC, 50 Hz / 60 Hz single phase |
| Current consumption | max. 16 A |
| Required RCD | 300 mA |
| Control cable | Fiber optic lines |
| Remote control via | LAN (TCP/IP); (IEEE only with NCD) |
| Interference suppression | 20 dB under limits DIN EN 55011:2018-05 class B |
| Total weight | approx. 80 kg |
| Operating temperature | 10°C-35°C |
| Accessories | Service manual 3 m power supply cable 15 m pneumatic air hose 8 mm 1 x pneumatic feed through |

Phone: +49(0)9606 923913-0
 Fax: +49(0)9606 923913-29

eMail: info@matur-gmbh.de
 Web: www.matur-gmbh.de

Sales Partner:



ABSOLUTE EMC LLC.
 Covering sales in North America
 United States, Mexico, & Canada

absolute-emc.com
 Phone:703-774-7505
info@absolute-emc.com

Brief description

The Compact Antenna Mast **CAM 6.0-P-12kg** is suitable in magnetic absorption chambers. The antenna mast, with the exception of the drive unit, is fabricated from plastic (PVC and reinforced fiberglass). Metal parts are located only in the base plate and the drive mechanism (max. 0.3 m above ground level).

Antenna Adapters for all commercially available antennas are available upon request. All antennas during polarization rotate around their axis to eliminate any elevation errors.

The **LAN (TCP/IP) - interface** provides an additional control option for all functions, when operated with the **FCU³⁰ or NCD Controller**.



Information presented enclosed is subject to change as product enhancements are made regularly. Pictures included are for illustration purposes only and do not represent all possible configurations.

Sales Partner:



ABSOLUTE EMC LLC.
Covering sales in North America
United States, Mexico, & Canada

absolute-emc.com
Phone: 703-774-7505
info@absolute-emc.com