

VBA0860-15

800MHz-6000MHz 15W Amplifier



Vectawave

- GaN technology
- **Class A** for maximum mismatch drive
- Featuring high efficiency proprietary Quadrature Hybrid designs

The VBA0860-15 is a 800-6000MHz high power amplifier designed for applications where a rugged Class A mismatch tolerant amplifier is required.

The amplifier is based on high performance extra wideband GaN output stages and utilizes Vectawave proprietary Quadrature Hybrid combining techniques, minimizing loss for a more efficient solution.

The amplifier can be controlled remotely via the Ethernet, USB and GPIB interfaces. The digital interface system manages enabling and disabling the amplifier, monitoring power supply health, communicating with the control computer and implementing electrical interlocks.

The amplifier operates in class A, with very low distortion and tolerance of 100% mismatch without foldback. See overleaf for technical specification.

VECTAWAVE TECHNOLOGY LIMITED
UNIT D THE APEX ST CROSS BUSINESS PARK
MONKS BROOK NEWPORT
ISLE OF WIGHT PO30 5XW
UNITED KINGDOM

Sales Partner:



ABSOLUTE EMC Llc.
Covering sales in North America
United States, Mexico, & Canada

absolute-emc.com
Phone: 703-774-7505
info@absolute-emc.com

Technical Specification

Electrical

<i>Frequency Range (Instantaneous)</i>	800-6000MHz
<i>Rated Output Power</i>	15W
<i>Output Power at 1dB Gain Compression</i>	10W
<i>Gain</i>	43dB Min
<i>Third Order Intercept Point (see note 1)</i>	51dBm
<i>Gain variation with Frequency</i>	±3dB
<i>Harmonics at rated linear power</i>	Better than -20dBc (1-6GHz) Better than -14dBc (0.8-1GHz)
<i>Output Impedance</i>	50 Ohms
<i>Stability</i>	Unconditional
<i>Output VSWR Tolerance (see note 2)</i>	Infinity any phase
<i>Input VSWR</i>	2:1 (Max)
<i>Supply Voltage</i>	100-240Vac (+/- 10%)
<i>Supply Frequency Range</i>	45-63Hz
<i>Supply Power</i>	150VA
<i>Mains Connector</i>	IEC320 –C14

Mechanical

<i>RF Connector Style</i>	Input type N female, output N female
<i>Safety Interlock</i>	2 x BNC, S/C and O/C to mute
<i>Communication Interface</i>	USB/GPIB/Ethernet
<i>Dimensions</i>	3U Rack, 500mm deep
<i>Mass</i>	6kg
<i>Operating Temperature Range</i>	0-40°C
<i>Case Style Options</i>	Rack Mountable or Bench top with rear or front panel connectors

Regulatory Compliance

<i>Conducted and Radiated Emissions</i>	EN61326 Class A
<i>Conducted and Radiated Immunity</i>	EN61326:2013 Table 1
<i>Safety</i>	EN61010-1

Notes

- 1 The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.
- 2 Output VSWR tolerance is specified for excitation within the permitted levels and frequency range.

Sales Partner:



ABSOLUTE EMC Llc.
Covering sales in North America
United States, Mexico, & Canada

absolute-emc.com
Phone:703-774-7505
info@absolute-emc.com

